ALIGNMENT COMBOS



	HOFCOMB01	\$36,999.99
HOFEELR709A	Hofmann 12,000 Lbs. Scissor Alignment Lift	\$16,999.99
HOFEEWA712AL	Hofmann geoliner™ 650 Imaging Wheel Aligner	\$16,499.99
HOFEAK0289J06	Premium Turn Plates (Set of Two)	\$1,149.99
	TOTALS	\$34,649.97
	SAVINGS	\$2,350.02

Roll Back Kit HOFEAK0277J28A With Purchase of: HOFCOMBO1 SKU 818791 | Part# HOFCOMB1 Offer Good Through December 31, 2016 - While Supplies Last



HOFEAK0289J06

stallation or Optional

	ALIGNCOMB05	\$31,999.99
FORCRA14	Forward Lift 14,000 Lb. 4 Post Alignment Lift	\$11,449.99
HOFEEWA715H	Geoliner 670XD	\$21,999.99
FORRRJ70G	7,000 Lbs. Rolling Jacks (Set of Two)	INCLUDED
	Airline Kit	INCLUDED
	TOTALS	\$33,449,98
	SAVINGS	\$1,449.99

Available via Outside Buv/EPO Lift Gate Service SKU 290017 HOFLIFTGATE 9500 HOFEEWA715H

FORRRJ70G

46

Prices Subject to Change Without Notice. Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-AZTOOL1.

Leasing Terms Available!* Ask Your AutoZone®

Commercial Sales Manager

SAVE OVER \$1,600

Tool & Equipment QUARTERLY

107



- Acme Threaded Screw for 8" Adjustment
- Bearing Mounted Spin Handle

• Support Range from 68" to 76'

- Complies With ASME PALD/2009 Safety Standards
- 24" Triangular Base and 3.25" Square Saddle Provides Additional Stability
- 45.25" Long Pump Handle for Easy Pumping Under Load
- Dual Pump Piston Power Unit Raises Saddle to Maximum Height in 6.5 Full Incremental Strokes
- Load-Limiting and Bypass Valves to Prevent Use Beyond Rated Capacity

• Lift Range from 3.5" to 18.1"

- Saddle Diameter 4.3'
- Complies With ASME PALD/2009 Safety Standards

• 50" Long Pump Handle for Easy Pumping Under Load

- Dual Pump Piston Power Unit Raises Saddle to Maximum Height in 8 Full Incremental Strokes
- Load-Limiting and Bypass Valves to Prevent Use Beyond Rated Capacity

• Lift Range from 3.5" to 21.375"

 Complies With ASME PALD/2009 Safety Standards



SKU 079534 KTI62110

- 1000 Lb. Capacity Foldable Engine Stand
- Worm Gear Driven Mounting Plate With Adjustable Fingers Rotates to Desired Position
- 4 Wheel Design With Locking Caster Wheels
- Made of Structural Steel Plate and Tubing for Added Strength
- Weighs 96 | bs
- Complies With ASME PALD/2009 Safety Standards



1.5 Ton Foldable Engine Crane SKU 079417

- **470**99 KTI63421
- 750 Lbs./ 1,500 Lbs./ 2,250 Lbs./ 3,000 Lbs. Capacity Engine Crane With 4 Different Boom Positions
- · Legs and Boom Fold Quickly for Storage
- Fast Rise Pump Without a Load
- 48" Long Boom With Chain and Swivel Hook Included
- 4.25" Low Profile Base for Easy Access Under Low Ground Clearance Vehicles
- Complies With ASME PALD/2009 Safety Standards



All K TOOL INTERNATIONAL Items Shown Are Covered By A 2 Year Warranty On Material And Workmanship

